

KU36

Ultra slim, high power
sub woofer

PRELIMINARY

DATASHEET



Features:

- Unique performance-to-size ratio
- 6" long-excursion woofer
- Double 6" passive radiator
- Extended frequency response
- Electronically protected
- Integrated flying points
- Double voice coil ($4\Omega+4\Omega$)
- Top quality components for outstanding performance
- Weather proof, suitable for outdoor installations
- Available in black or white

Applications:

- Theatre, Club, Churches
- To extend the low range in small and midium rooms
- Portable and installed AV systems
- Stage and AV studio monitoring

KU36	
Acoustics	
Power handling	2 X 80 W ^(AES)
Impedance	2 X 4Ω
Operating frequency range	45 Hz - 300 KHz.
SPL 1W / 1mt	89 dB
Maximum SPL	115 dB continuous - 121 dB peak
Transducers	
Full range	1 X 6" Neodymium magnet with 1.5" voice coil + 2 X 6" passive transducer
Audio Input	
Connectors	4-pin Phoenix
Wiring	Pin1=Ch 1-, Pin2=Ch 1+, Pin3=Ch 2-, Pin4=Ch 2+
Recommended Amplifiers	
KA1-1, KA3-3, KA7-7, KA10-10	
Physical	
Dimensions	50.7 x 17.5 x 10.6 cm (19.96" x 6.89" x 4.17")
Weight	6.4 Kg (14.11 lbs)
New materials and design are introduced into existing products without previous notice. Present systems may differ in some respects from those presented in this brochure.	

www.k-array.com

HP Sound Equipment s.r.l. Viale Roma 7/i - 50037 - San Piero a Sieve (FI), Italy
tel. +39 055 8487222 - fax. +39 055 8487238 - e-mail: info@k-array.com